

Ohio StreamStats Flow Worksheet

1. Fill Site Information	
1a. Site Description / Designator CTFD 1	1c. Fill Site Bottom Substrate → Exploitable Fraction 3 - Silt / Sand 0.5
1b. Site Location SR-180 bridge east of Hallsville, OH	1d. Minimum Acceptable Flow 250 GPM

2. Flow Estimates							
Month	StreamStats Data			Conversion to GPM			Exploitable Flow (GPM)
	StreamStats Statistic	Flow (CFS)	Prediction Error (%)	Min Flow (GPM)	Average Flow (GPM)	Max Flow (GPM)	
JAN	Q1	1.34	17	499	601	704	250
FEB	Q2	1.75	17	652	785	919	326
MAR	Q3	1.88	17	700	844	987	350
APR	Q4	1.80	17	671	808	945	335
MAY	Q5	1.24	17	462	557	651	231
JUN	Q6	0.72	17	268	323	378	134
JUL	Q7	0.40	17	149	180	210	75
AUG	Q8	0.29	17	108	130	152	54
SEP	Q9	0.16	17	60	72	84	30
OCT	Q10	0.17	17	63	76	89	32
NOV	Q11	0.45	17	168	202	236	84
DEC	Q12	0.93	17	346	417	488	173

